




BR-40 2P

Type 2 Surge Arrester



■ BR-40 2 pole surge arrester is suitable for single phase TN system.

		BR-40 690 2P	BR-40 1000 2P
SPD classification according to EN61643-11		Type 2	Type 2
SPD classification according to IEC61643-11		Class II	Class II
Max. continuous operating a.c. voltage	Uc	690V	1000V
Nominal discharge current (8/20μs)	In	20kA	20kA
Max. discharge current (8/20μs)	Imax	40kA	40kA
Voltage protection level	Up	≤2.0kV	≤2.0kV
Voltage protection level 5kA	Up	≤1.6kV	≤1.6kV
Max. backup fuse		125A gG	125A gG
Short-circuit withstand capacity	ISCCR	25kA	25kA
Temporary overvoltage TOV-withstand	UT	880V/5sec.	1300V/5sec.
Temporary overvoltage TOV-safe failure	UT	1100V/120min.	1700V/120min.
Leakage current	IPE	<1mA	<1mA
Response time	tA	≤25ns	≤25ns
Operating temperature range	Tu	-40°C-80°C	-40°C-80°C
Operating state/fault indication		green/red	green/red
Cross-section area (Min.)		4 mm ²	4 mm ²
Cross-section area (Max.)		35mm ²	35mm ²
For mounting on		35mm Din rail	
Enclosure material		Thermoplastic UL94-V0	
Degree of protection		IP20	IP20
Order Code		B18032	B18048
Order Code (With remote signaling)		B18033	B18049