




BR-25VG 1+1

Type 1+Type 2+Type 3
Surge Arrester



■ BR-25VG 1+1 is suitable for single phase TT and TN system.

		BR-25VG 320 1+1	BR-25VG 440 1+1	BR-25VG 690 1+1
SPD classification according to EN61643-11		Type 1 + Type 2 + Type 3	Type 1 + Type 2 + Type 3	Type 1 + Type 2 + Type 3
SPD classification according to IEC61643-11		Class I + Class II + Class III	Class I + Class II + Class III	Class I + Class II + Class III
Nominal operating voltage	Un	250/440V(50/60Hz)	250/440V(50/60Hz)	400/690V(50/60Hz)
Max. continuous operating a.c. voltage	Uc (L-N/N-PE)	320V/255V(50/60Hz)	440V/255V(50/60Hz)	690V/255V(50/60Hz)
Lightning impulse current (10/350µs)	Iimp (L-N/N-PE)	25kA/50kA	25kA/50kA	25kA/50kA
Total discharge current (10/350µs)	Itotal	50kA	50kA	50kA
Nominal discharge current (8/20µs)	In (L-N/N-PE)	30kA/50kA	30kA/50kA	30kA/50kA
Maximum discharge current (8/20µs)	I _{max} (L-N/N-PE)	70kA/100kA	70kA/100kA	70kA/100kA
Quantity of electric charge (L-N,N-PE)	Q	12.5As, 25As	12.5As, 25As	12.5As, 25As
Specific energy (L-N,N-PE)	W/R	156kJ/Ω, 625kJ/Ω	156kJ/Ω, 625kJ/Ω	156kJ/Ω, 625kJ/Ω
Voltage protection level	Up (L-N/N-PE)	≤1.5 kV/≤1.5kV	≤1.8 kV/≤1.5kV	≤2.5kV/≤1.5kV
Short-circuit current rating a.c.	I _{SCCR} (L-N/N-PE)	25kA rms/100A rms	25kA rms/100A rms	25kA rms/100A rms
Max. backup fuse		200A gG	200A gG	200A gG
Temporary overvoltage TOV-withstand	UT (L-N)	350V/5sec.	580V/5sec.	880V/5sec.
Temporary overvoltage TOV-safe failure	UT (L-N)	550V/120min.	770V/120min.	1100V/120min.
Temporary overvoltage TOV-withstand	UT (N-PE)	1200V/200ms	1200V/200ms	1200V/200ms
Leakage current	I _{PE}	0mA	0mA	0mA
Response time	t _A	≤25ns/≤100ns	≤25ns/≤100ns	≤25ns/≤100ns
Operating temperature range	Tu	-40°C-80°C	-40°C-80°C	-40°C-80°C
Cross-section area (Min.)		4mm ²	4mm ²	4mm ²
Cross-section area(Max.)		35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail	35mm Din rail	35mm Din rail
Enclosure material		Thermoplastic UL94-V0	Thermoplastic UL94-V0	Thermoplastic UL94-V0
Degree of protection		IP20	IP20	IP20
Order Code		B17271	B17283	B17295
Order Code (With remote signaling)		B17272	B17284	B17296