




## BR-60 4P

### Type 2 Surge Arrester



BR-60 4 pole surge arrester is suitable for TN-S system.

	BR-60 150 4P	BR-60 275 4P	BR-60 320 4P	BR-60 385 4P
SPD classification according to EN61643-11	Type 2	Type 2	Type 2	Type 2
SPD classification according to IEC61643-11	Class II	Class II	Class II	Class II
Max. continuous operating a.c. voltage	Uc	150V	275V	320V
Nominal discharge current (8/20μs)	In	30kA	30kA	30kA
Max. discharge current (8/20μs)	Imax	60kA	60kA	60kA
Voltage protection level	Up	≤1.0kV	≤1.6kV	≤1.8kV
Voltage protection level 5kA	Up	≤0.5kV	≤0.6kV	≤1.2kV
Max. backup fuse		160A gG	160A gG	160A gG
Short-circuit withstand capacity	IscCR	25kA	25kA	25kA
Temporary overvoltage TOV-withstand	UT	180V/5sec.	335V/5sec.	400V/5sec.
Temporary overvoltage TOV-safe failure	UT	230V/120min.	440V/120min.	520V/120min.
Response time	tA	≤25ns	≤25ns	≤25ns
Operating temperature range	Tu	-40°C-80°C	-40°C-80°C	-40°C-80°C
Operating state/fault indication		green/red	green/red	green/red
Cross-section area (Min.)		4 mm <sup>2</sup>	4 mm <sup>2</sup>	4 mm <sup>2</sup>
Cross-section area (Max.)		35mm <sup>2</sup>	35mm <sup>2</sup>	35mm <sup>2</sup>
For mounting on	35mm Din rail			
Enclosure material	Thermoplastic UL94-V0			
Degree of protection	IP20	IP20	IP20	IP20
Order Code	B18761	B18763	B18765	B18767
Order Code (With remote signaling)	B18762	B18764	B18766	B18768