




BRSCB-I-12.5

MCB for Surge Arrester

MCB specially designed for Surge Arrester It can cut the leakage current to 3A.

Therefore prevent possible fire hazzard caused by degenerated SPD.



■ Special MCB designed to protect the SPD.

		BRSCB-I-12.5-4P	BRSCB-I-12.5-3P	BRSCB-I-12.5-2P	BRSCB-I-12.5-1P
Nominal a.c. voltage	Un	500V	500V	500V	500V
Impluse current (10/350µs)	Iimp	12.5kA	12.5kA	12.5kA	12.5kA
Nominal discharge current (8/20µs)	In	25kA	25kA	25kA	25kA
Max. discharge current (8/20µs)	I _{max}	60kA	60kA	60kA	60kA
Operating temperature range	Tu	-40°C-80°C	-40°C-80°C	-40°C-80°C	-40°C-80°C
Operating state/fault indication		green/red	green/red	green/red	green/red
Cross-section area (Min.)		2.5mm ²	2.5mm ²	2.5mm ²	2.5mm ²
Cross-section area (Max.)		35mm ²	35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail	35mm Din rail	35mm Din rail	35mm Din rail
Enclosure material		Thermoplastic UL94-V0			
Degree of protection		IP20	IP20	IP20	IP20
Order Code		B8488	B8489	B8490	B8491